



Shaft Dia.	1/8	3/16	1/4	5/16	3/8
P/N	PK18-MSB NY18-MSB	PK316-MSB NY316-MSB	PK14-MSB NY14-MSB	PK516-MSB NY516-MSB	PK38-MSB NY38-MSB
Dimensions					
I.D.	.125	.188	.250	.313	.375
O.D.	.250	.313	.400	.500	.595
L	.825	.985	1.075	1.320	1.500
W	.520	.560	.590	.710	.800
A	.475	.585	.700	.830	1.000
H	.200	.285	.310	.350	.410
T	.135	.160	.155	.160	.170
C	.140	.140	.140	.168	.168

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **Technique Eng., Inc.** ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **Technique Eng., Inc.** IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE			
		DIMENSIONS ARE IN INCHES	DRAWN	D.A.	15.04.12			
		TOLERANCES:	CHECKED			TITLE:		
		FRACTIONAL ±	ENG APPR.			Mounted Sleeve Bearings/Bushings		
		ANGULAR: MACH ± BEND ±	MFG APPR.					General Dimensions
		TWO PLACE DECIMAL ±.01	Q.A.			SIZE	DWG. NO.	
		THREE PLACE DECIMAL ±.005	COMMENTS:			A	07042012	A
		INTERPRET GEOMETRIC TOLERANCING PER:				SCALE: 2:1 WEIGHT: SHEET 1 OF 1		
		MATERIAL						
		Victrex WG101						
		FINISH						
NEXT ASSY	USED ON							
APPLICATION		DO NOT SCALE DRAWING						